



# QUARTZ 3000 20W50



Multigrade oil for Gasoline engines.

## APPLICATIONS

- For lubrication of all gasoline engines
- Designed to meet all operating condition (city, rural and highway)
- Best suitable for the vehicles made before 1996

## SPECIFICATION

- International Standards
- API : SJ

## ADVANTAGES

- Infusion of Detergent/Dispersant properties helps in preventing the built up of engine deposits as well as by holding the insolubles/oxidative product in suspension
- Excellent thermal stability enhances the life of oil
- Stable to mechanical and thermal Shear, thus exhibit "stay in grade" characteristics even after prolonged usage.

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	QUARTZ 3000 20W50
Density at 29.5°C, kg/l	D 4052	0.870
Kinematic viscosity at 100°C, cSt	D 445	18.03
Viscosity Index	D 2270	131
Pour point, °C	D 97	- 24
Total Base Number, mg KOH/g	D 2896 (B)	6.34
Flash point COC, °C	D 92	234

(Above characteristics are mean values given as an information)

### TOTAL OIL INDIA PVT LTD.

Head Office : 3<sup>rd</sup> Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720  
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,  
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from : [www.total.co.in](http://www.total.co.in)  
Date 01/12